# HOW ADVANCED WALLING SYSTEMS CAN PRODUCE SUSTAINABLE OUTCOMES IN THE BUILT ENVIRONMENT

**CPD PRESENTATION** 



#### INTRODUCTION

- THIS SESSION AIMS TO EXPLORE EVOLVING TRENDS IN WALLING SYSTEMS AND ITS RELATIONSHIP WITH SUSTAINABLE CONSTRUCTION METHODS
- OFFSITE CONSTRUCTION CONTRIBUTES TO NET ENERGY SAVINGS
- FIRE SAFETY CONSIDERATIONS AND THE REQUIREMENT FOR CLASS A RATED CONSTRUCTION MATERIALS



#### WHO ARE WE?

- MANUFACTURERS AND SUPPLIERS OF AN ADVANCED WALLING SYSTEM THAT PROVIDES AN ALTERNATIVE TO TRADITIONAL BLOCKWORK, SFS AND PLASTERBOARD SYSTEMS
- BASED IN MANCHESTER WITH A LONDON & MANCHESTER SHOWROOM
- PART OF THE PROPERTY ALLIANCE GROUP & HARWAL GROUP





## AIMS AND OBJECTIVES



- I. UNDERSTAND THE CONCEPT OF DESIGNING OUT WASTE AND ITS IMPACT ON SUSTAINABLE PRACTICES WITHIN THE BUILT ENVIRONMENT
- 2. CONSIDER HOW RECENT CHANGES IN
  BUILDING REGULATIONS CAN, AND SHOULD,
  INFLUENCE YOUR DESIGN STRATEGY FOR PRODUCING
  FIRE SAFE BUILDINGS
- 3. LEARN HOW ADVANCED WALL SYSTEMS ARE BEING UTILISED IN THE CONSTRUCTION OF INTERIOR AND EXTERIOR WALL ASSEMBLIES
- 4. GET A BETTER UNDERSTANDING OF HOW THESE SYSTEMS ARE BEING INSTALLED ON SITE

#### LEARNING OBJECTIVES



# CONSTRUCTION WASTE REDUCTION BY DESIGN



#### A STUDY FOUND...


... waste management is not a priority in the design process.


Additionally, the architects seemed to take the view that waste is *mainly* produced during site operations and *rarely* generated during the design stages; however, about one-third of construction waste could essentially arise from design decisions.

Osmani, Glass & Price (2008)



#### MATERIALS RESOURCE EFFICIENCY







## WALL CONSTRUCTION





PRIVACY AND ACOUSTICS








### WALL CONSTRUCTION





#### SOUND INSULATION



- APPROVED DOCUMENT E
- THE REDUCTION IN SOUND ACROSS A PARTITION
- DOES NOT DESCRIBE THE LEVEL
   OF SOUND LOST WITHIN AN
   ADJACENT ROOM



**FIRE SAFETY** 

- APPROVED DOCUMENT B
- A NEW WALL MAY AFFECT THE MEANS OF FIRE ESCAPE
- AN ESCAPE WINDOW AND ONE OR MORE SMOKE ALARMS MAY BE NEEDED
- SOME WALLS AROUND STAIRWAYS
  WILL NEED TO HAVE FIRE
  RESISTANCE, EVEN IF HOUSES ARE
  TWO STOREYS OR LESS
- THE REMOVAL OF AN INTERNAL WALL SHOULD BE CAREFULLY CONSIDERED
- OTHER FIRE-RESISTANT FITTINGS
   MAY BE NEEDED (E.G. FIRE DOORS)

HM Government

The Building Regulations 2010

Fire safety

B

#### APPROVED DOCUMENT

#### Volume 1: Dwellings

Requirement B1: Means of warning and escape Requirement B2: Internal fire spread (linings) Requirement B3: Internal fire spread (structure)


Requirement B4: External fire spread

Requirement B5: Access and facilities for the fire service

Regulations: 6(3), 7(2) and 38

2019 edition incorporating 2020 amendments – for use in England

ONLINE VERSION



**INTERNAL WALLS** 

- APPROVAL UNDER BUILDING REGULATIONS 2010
- CONVERSION PROJECTS
  - Adequate separation
  - Adequate fire resistance
  - May need to provide sound insulation



The Building Regulations 2010

The Merged Approved Documents



For use in England

July 2021 compilation of individual approved documents



STRUCTURAL SUPPORT

#### NON-LOAD BEARING

Walls that provide separation between rooms and are not required to transfer loads

#### LOAD BEARING

Where the wall provides separation between rooms and is also required to transfer loads from other parts of the structure, roof and floors etc., Down to the foundations



#### **BLOCKWORK**

ADVANTAGES	CONSIDERATIONS		
Solidity & Strength	Expensive		
Good Soundproofing	Time consuming		
Fire resistant	Multiple visits to the work face by trades		
	Requires scaffold		
	Debris & waste		
	More men on site		
	Heavy		



**Reference** 

- BLOCKWORK
- DRYLINING/PLASTERBOARD
  - STEEL FRAME SYSTEMS (SFS)

## DRYLINING/PLASTERBOARD

ADVANTAGES	CONSIDERATIONS		
Economical	Multiple parts for construction		
Improved thermal efficiency	Easily damaged		
Acoustic performance	More men on site		
Fire performance	Patressing for installation of fittings		
	Many different wall types		
	Complex details for fire stopping		
	High wastage		



<u>Reference</u>

- DRYLINING/PLASTERBOARD
- STEEL FRAME SYSTEMS (SFS)

## STEEL FRAME SYSTEMS (SFS)

ADVANTAGES	CONSIDERATIONS		
Economical	Multiple parts for construction		
Improved thermal efficiency	More men on site		
	Patressing for installation of fittings		
	Complex details for fire stopping		



**Reference** 

- BLOCKWORK
- DRYLINING/PLASTERBOARD
  - STEEL FRAME SYSTEMS (SFS)

# A MODERN APPROACH TO WALL CONSTRUCTION




#### A MODERN APPROACH TO WALL CONSTRUCTION

- ADVANCED WALLING SYSTEM
- CONSTRUCTED OF A PATENTED CONCRETE-BASED INNER MIXTURE WHICH IS ENCAPSULATED BY TWO FCBs
- NOT AFFECTED BY WATER OR MOULD, CAN BE INSTALLED BEFORE BUILDING IS WATERTIGHT
- OFF-SITE MANUFACTURE
- AN ALTERNATIVE TO:
  - Blockwork
  - SFS
  - Drylining/plasterboard systems
  - Risers
  - Lift shafts
  - Concrete cores and stairwells
  - Bathroom pods



# OFF-SITE MANUFACTURE






#### FIRE-RATED ADHESIVE MUST BE USED DURING INSTALLATION



WALL IS INSTALLED UP TO STRUCTURAL SOFFIT, REDUCING COSTLY FIRE STOPPING



TWO THICKNESSES: 75MM AND 100MM = UP TO (AND OVER) FOUR HOURS' FIRE RESISTANCE





**LESS MAINTENANCE REQUIRED** 



DAMAGE CAN BE EASILY REPAIRED



**WALLS CAN BE RECONFIGURED** 



DESIGN AMENDMENTS CAN BE ACCOMODATED

# HEALTH & SAFETY AND LONG-TERM MAINTENANCE ISSUES

If installing at height, cite Regulation 9.2 of the CDM Regulations 2015; regarding the principles of prevention from falls.



Please note: Tests have been undertaken on a prototype, load bearing panel. This new system is expected to be launched in 2022.

# INAPPROPRIATE APPLICATIONS/USES

## AN OBJECTIVE COMPARISON



#### AN OBJECTIVE COMPARISON

	75MM ADVANCED WALL SYSTEMS	100MM ADVANCED WALL SYSTEMS	PLASTERBOARD	AAC BLOCK
Fire Rating	2 hours	4 hours	2 hours	Max 3 hours
Acoustic Rating (dB Rw)	40 db	45 db	Varies	Up to 39 db
U-Value	1.52	1.25	2.3-2.8	0.3-0.4
Wet Areas	Acceptable	Acceptable	Requires treatment	Requires treatment
Plaster Requirements	Not required	Not required	-	Required
Wet Trades	Not required	Not required	Required	Required
Wastage	3%	3%	Around 25%	Around 20%
Manpower	50% Less	50% Less	100%	100%
Lintels	Not required	Not required	Required	Required

### CONSIDERATIONS



## WHAT TO CONSIDER WHEN SPECIFYING WALLING SYSTEMS













**LABOUR** 

**PROGRAMME TIME** 

COST

**WATER RESISTANCE** 


**SUSTAINABILITY** 

**EFFICIENCY** 


## CASE STUDIES



# CASE STUDY #1: OXYGEN



CASE STUDY #2:
ANGEL
MEADOWS



# RE-CAP LEARNING OBJECTIVE

- A FRESH PERSPECTIVE ON THE NOTION OF 'DESIGNING OUT WASTE'
- DEVELOPED YOUR UNDERSTANDING OF DIFFERENT WALL SYSTEMS
- STARTED TO THINK DIFFERENTLY ABOUT THE PRODUCTS AND SOLUTIONS YOU SPECIFY




#### **CONTACT US**

#### +44 (0) 161 511 4790

sales@specwall.com media@specwall.com

Alliance House Westpoint Enterprise Park Clarence Ave Manchester, M17 IQS



#### **Showroom North**

St Mary's Parsonage, Manchester M3 2PN

#### **Showroom South**

The Building Centre, 26 Store St, London WCIE 7BT